

TYPE:

PRECOMPRESSION SPRAYER "SOFIA TEC" (version with EPDM o-ring)

• TECHNICAL FEATURES

- Precompression sprayer, manual working
- Article with EPDM o-rings for aggressive industrial liquids (diluted): building oils, solvents, detergents for the sanitation, surface cleaning and cars prewashing. Suitable also for hydrocarbons, oils, acid and basic solutions, and in agricultural field to spray pesticide liquids, insecticides, herbicides, fertilizers, preservatives.
It's recommended to do a compatibility test before use and to rinse the sprayer with clean water after each use.
- Thermoplastic anti-UV tank
- Reading scale – division 1 liter divisione
- Unscrewable plastic piston with EPDM o-rings
- Security valve – automatic set-up pressure discharge (3 bar)
- Lance with special o-rings: plastic lever handle, aluminium extension, brass adjustable nozzle
- Colors: white tank
- Equipped with strap for easy carrying
- Operation and maintenance manual
- Single box

• TECHNICAL DATA

TANK CAPACITY	LT . 6	
AVERAGE WORKING PRESSURE	BAR 2,5	
MAX WORKING PRESSURE	BAR 3	
LANCE	ALUMINIUM	
NOZZLE	BRASS	
HANDLE	PLASTIC	
NOZZLE PERFORMANCE (2,5 BAR)	MIST	STRAIGHT
MAX DELIVERY L / MIN.	0,6	1,1
SPRAING ANGLE	30 °	-----
MAX SPRAYING (LENGHT) CM.	-----	700
MAX SPRAYING (HEIGHT) CM.	-----	550
EMPTY WEIGHT LT. 6	KG. 1,30	



DATE: 10 / 01 / 2020

TECHNICAL OFFICE : DAL DEGAN ALBERTO

The company DAL DEGAN SERVICE SRL - VIA TURRA, 45 - 36064 MASON VICENTINO (VI) – ITALY declares that the above mentioned sprayers are in accordance with the technical data above stated and respect the security issues as per “Directive 2006/42/CE”.



DAL DEGAN SERVICE