

TYPE:

PRECOMPRESSION SPRAYER "CARIBE 8"

• TECHNICAL FEATURES

- Precompression sprayer, manual working
- Article with special rubber seals for aggressive liquids (diluted) in buildings or for disinfections, industrial treatments and environmental sanitization
It's recommended to do a compatibility test before use and to rinse the sprayer with clean water after each use.
- Innovative polypropilene injection twin moulded tank and welded by an ultrasounds system
- Thermoplastic anti-UV tank
- Professional brass piston
- Security valve – automatic set-up pressure discharge (3,5 bar)
- Lance with special o-rings: brass lever handle, straight stainless steel extension, brass adjustable nozzle
- Equipped with strap for easy carrying
- Operation and maintenance manual
- Single box

• TECHNICAL DATA

TANK CAPACITY	LT . 8	
MAX WORKING PRESSURE	BAR 3,5	
LANCE	INOX STRAIGHT	
NOZZLE	BRASS	
HANDLE	BRASS	
NOZZLE PERFORMANCE (3,5 BAR)	MIST	STRAIGHT
MAX DELIVERY L / MIN.	0,6	1,1
SPRAY ANGLE	30 °	-----
MAX SPRAYING (LENGHT) CM.	-----	700
MAX SPRAYING (HEIGHT) CM.	-----	550
EMPTY WEIGHT LT. 8	KG. 2,5	



DATE: 01 / 01 / 2021

TECHNICAL OFFICE : DAL DEGAN ALBERTO

The company DAL DEGAN SERVICE SRL - VIA TURRA, 45 - 36064 MASON VICENTINO (VI) – ITALY declares that the above mentioned sprayers are in accordance with the technical data above stated and respect the security issues as per “Directive 2006/42/CE”.



DAL DEGAN SERVICE