


**Swingfog SN 50**




Spraying tank, stainless steel,  
capacity 6.5 l, Swingfog SN 50




Spraying tank, polyethylene,  
capacity 7 l, Swingfog SN 50 PE




Spraying tank, stainless steel,  
capacity 9 l, Swingfog SN 50-10



Spraying tank, polyethylene,  
capacity 10 l, Swingfog SN 50-10 PE



Standard fogging tube for  
oil-based fogging mixtures



High performance fogging tube for  
water-based fogging mixtures only

## TECHNOLOGY FOR PROFESSIONALS



Swingfog – the optimal machines for Vector and Pest Control. Plant Protection in Greenhouses and Plantations. Disinfection in Food Processing and Animal Production. Stock Protection in Warehouses. Anti-Sprouting Treatment of Potatoes.



**swingfog® + fontan®**  
QUALITY WINS

Technical data

Swingfog SN 50 (all versions)

|   |  |              |                  |   |
|---|--|--------------|------------------|---|
| Power, combustion chamber   | 18.7 kW/25.4 hp (16,100 kcal/h)  |              |                  |   |
| Fuel tank   |  |              |                  |   |
| Stainless steel, capacity   | approx. 1.4 l  |              |                  |   |
| Feed pressure   | approx. 0.12 up to 0.13 bar  |              |                  |   |
| Fuel  | standard grade petrol, leaded or unleaded, at least 74 octane  |              |                  |   |
| Fuel consumption  | approx. 2 l/h  |              |                  |   |
| Spraying tank   | SN 50  | SN 50 PE     | SN 50-10         | SN 50-10 PE   |
| Capacity  | 6.5 l  | 7.0 l        | 9.0 l            | 10.0 l  |
|   | stainless steel  | polyethylene | stainless steel  | polyethylene  |
| Feed pressure   | approx. 0.3 up to 0.35 bar (depending on dosage nozzle used)   |              |                  |   |
| Ignition  | electronic ignition coil,<br>4 dry batteries 1.5 V each in series, negative on ground (optional accessory)   |              |                  |   |
| Output  | dosage nozzles, stainless steel  |              |                  |   |
| (measured with water, approx.)  | 0.7  | 10 l/h       |                  |   |
|   | 0.8  | 14 l/h       |                  |   |
|   | 0.9  | 17.5 l/h     |                  |   |
|   | 1.0  | 20.5 l/h     |                  |   |
|   | 1.1  | 23.5 l/h     |                  |   |
|   | 1.2  | 27 l/h       |                  |   |
|   | 1.4  | 32 l/h       |                  |   |
|   | 1.7  | 42 l/h       |                  |   |
| Dimensions  | SN 50/SN 50 PE:  |              | 133 x 29 x 33 cm |   |
|   | SN 50-10/SN 50-10 PE:  |              | 133 x 34 x 33 cm |   |
| Weight (empty)  | SN 50  | SN 50 PE     | SN 50-10         | SN 50-10 PE   |
|   | 8.75 kg  | 8.7 kg       | 9.1 kg           | 9.0 kg  |
| Automatic chemical solution cut-off device  | all Swingfog SN 50 versions can also be supplied with<br>factory-mounted automatic chemical solution cut-off<br>device for the fogging mixture   |              |                  |   |
| Special version Swingfog SN 50 A  | with factory-mounted automatic chemical solution<br>cut-off device and special fog outlet to fog directly into<br>smallest holes and into sewage systems.<br>Available with the following spraying tanks:<br>SN 50/A, 6.5 l, stainless steel<br>SN 50 PE/A, 7.0 l, polyethylene<br>SN 50-10/A, 9.0 l, stainless steel<br>SN 50-10 PE/A, 10.0 l, polyethylene |              |                  |  |
| Standard accessories  | fogging tube, stainless steel  |              |                  |   |
| for all versions  | dosage nozzles, stainless steel 0.8 / 1.0 / 1.2 (nozzle 1.0 already installed)   |              |                  |   |
|   | fuel funnel with strainer (mesh width 0.1 mm, stainless steel)   |              |                  |   |
|   | chemical funnel with strainer (mesh width 0.1 mm, stainless steel)   |              |                  |   |
|   | filter insert spraying tank, stainless steel   |              |                  |   |
|   | tool kit   |              |                  |   |
|   | cleaning equipment   |              |                  |   |
|   | set of spares (gaskets, O-rings, diaphragms)   |              |                  |   |
|   | carrying strap   |              |                  |   |
|   | ear protection (2 sets)  |              |                  |   |
|   | dip stick/level indicator for spraying tank (for Swingfog SN 50 and SN 50-10 only)   |              |                  |   |
|   | instruction manual including spare parts list  |              |                  |   |
| Optional accessories  |  |              |                  |   |
| (available at extra charge)   |  |              |                  |   |
| for all versions  |  |              |                  |   |
| Dosage nozzles, stainless steel   | 0.7 / 0.9 / 1.1 / 1.4 / 1.7  |              |                  |   |
| High performance fogging tube, stainless steel<br>(solely for water-based fogging mixtures) | to optimize the droplet spectrum,<br>no deposits of larger drops in front of the unit  |              |                  |   |
| Silencer  | all versions   |              |                  |   |
| Manometer set   | for workshop use   |              |                  |   |